

OUR MOST SPACE EFFICIENT HOME LIFT

Aritco HomeLift Compact Datasheet 2025

Sometimes great things come in small packages. Our most space-efficient lift, the Aritco HomeLift Compact, opens up a world of possibilities in homes that were previously considered too limited in space for a lift. With its modern design, customizable features, and connectivity, the home lift offers the advantages of being small combined with the ability to think big.

Aritco HomeLift Compact offers you an unique Aritco Scandinavian design; a sleek platform design, a DesignWall and control panel with integrated handrail, double doors and contemporary and flexible shaft glass solutions. Accessible online via Aritco SmartLift.



 **ELEVÁRE**
CERTIFIED PARTNER OF ARITCO


ARITCOTM

Elevare Indonesia
Clon Park 32, Jakarta
Garden City Boulevard,
Cakung, Jakarta Timur


P : +62 811-800-8012
E : admin@elevareindonesia.com
W : elevareindonesia.com



Aritco HomeLift Compact

Aritco HomeLift blends refined design with full personalization. From the iconic DesignWall and ambient DesignLight, to elegant glass walls and ceiling patterns — every detail reflects your lifestyle. Choose from curated colors, floorings, and finishes. Powered by SmartLift technology for live updates and remote support, with SmartSafety features for quiet peace.

Sizes



SIZE	CARRIER SIZE (AxB)	FINISH SIZE (CxD)	RATED LOAD
C1	580 X 805 mm	840 x 880 mm	250 kg / 2 pers
C2	880 x 805 mm	1 140 x 880 mm	250 kg / 2 pers
C3	1 080 x 805 mm	1 340 x 880 mm	250 kg / 3 pers

DesignWall™



Lift colour

Comes in three standard colors, Traffic White (RAL9016), Jet Black (RAL 9005) and Anthracite Grey (RAL7016). Can be painted in any RAL color from the RAL K7 classic chart (Except for pearl and fluorescent colors)



Glass panel



Clear Glass
(Std.)



Tinted
(Opt.)

Floor



Tehnical compliance

European Machine Directive 2 006/42/EC | European Standard EN 81-41

Drive system

Patented screw-and-nut system

Rated speed

Max 0.15 m/s

Emergency lowering

Battery-powered

Travel height

1 000 mm

Number of Floors

2 - 6 floors

Installation

Recessed installation 37 mm below floor level / 0 mm with a ramp

Operation

One-touch operation (press one time)

Power supply

230 V 1-phase | 400 V 3-phase

Warranty

5-year product warranty and a 10-year drive technology warranty

